



ELLIX 45

SPECIFICATION

printing method	thermal line printing
print speed (maximum)	220mm/second
resolution(DPI)	180 DPI
MCBF	70,000,000Lines
Interface	USB Only, USB+RS-232, USB+PARALLEL, USB+ETHERNET, USB+WIFI, USB+BLUETOOTH, USB+RS-232+ETHERNET
barcode	UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Code 128, ITF, CODABAR, PDF417, QR Code
Auto cutter	1,600,000 cut
features	Jam Free (Uncloaked)/paper-feeding is made easy through application of Jam Free/Auto Cutter and options for functions like detachable/attachable panel and LCD are available. Display and change function is applied for Wall-mounting. (pending patent application)



ELLIX 35

SPECIFICATION

printing method	thermal line printing
print speed (maximum)	180mm/second
resolution(DPI)	180 DPI
MCBF	70,000,000Lines
Interface	USB+RS-232, USB+PARALLEL, USB+WI-FI, USB+RS-232+ETHERNET
barcode	UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Code 128, ITF, CODABAR, PDF417, QR CodeCode
Auto cutter	1,600,000 cut
features	Jam Free (Uncloaked)/paper-feeding is made easy through application of Jam Free/Auto Cutter and options for functions like detachable/attachable panel and LCD are available. Display and change function is applied for Wall-mounting. (pending patent application)



SRP-770 II

SPECIFICATION

printing method	Directer Thermal Printing
print speed	127mm/second (5inch/second)
letter assembly	7 types of bit map font, 7 code page, quadruple enlargement is possible, Support for BMP and PCX graphic, Enclosure of smooth font
Paper sheet types	label, tag, successive paper sheet, Fan-fold
product life cycle / durability of head	20,000,000 line / 50Km
bar code	Code 39, Code 128, interleave 2 of 5, Code Bar UPC-A, UPC-E, EAN-8, EAN-13, UCC-EAN128, Maxicode(2D), PDF 417(2D)
flash memory	1MB (8Mb)
sensor	Gap, Black mark, Notch Sensor
communication method	RS-232C, IEEE1284, USB (standard)
power source	AC 100 ~ 240V $\pm$ 10% (inclusion) DC 24V, 3.75A
communication	Serial port, Parallel port, USB(v1.1), LAN(option)
size	184×221×171mm
operation temperature	0 ~ 45°C